

# RUBBER BASED PSA



## PSA-7

### Product Application and Description:

PSA-7 is a general purpose rubber based pressure sensitive adhesive designed to provide aggressive quick tack and adhesion in a wide range of substrates including polyolefins and corrugated paper board. PSA-7 provides exceptional shear performance, while providing excellent substrate wet-out for fast ultimate bond strength.

### Shelf Life and Storage:

It is recommended to consume all materials within 1 year from date of purchase. Best if stored in a controlled environment (72°F and 50%RH) and out of direct sunlight.

Technical Data	
Test Method/Performance Parameter	Result/Performance Properties
180° Peel at 24 hours (PSTC-101)	4.6 lbs./in.
Loop Track	4.5 lbs./in.
Shear (1.00" X 1.00" X 1kg)	3.9 hours
Service Temperature	-20°F to 275°F (-29°C to 135°C)
Application Temperature	30°F to 120°F (-1°C to 49°C)
Tested at 1.0 mil of adhesive on 2.0 mil polyester film to Stainless Steel.	

The information contained herein is derived from data believed to be reliable and is presented to assist our customers in determining whether our products are suitable for use in their application. We request that our customers test our products before use to satisfy themselves as to suitability for use. No warranty or guarantee is expressed or implied. Protection from any law or patents is not inferred. All patent rights are reserved. The exclusive remedy for all proven claims is limited to replacement of our materials and in no event shall we be liable for special, incidental, or consequential damages. Customers desiring assistance with specification, development or performance criteria for specific product applications should contact us for further information.