

ALUMINUM TAPE



TP-AL1.5

Product Application and Description:

TP-AL1.5 is a 1.5 mil dead soft aluminum foil tape which incorporates a high performance acrylic pressure sensitive adhesive designed for general purpose, permanent name plate and laminating applications. TP-AL1.5 is provided with a 44# poly coated kraft liner.

Shelf Life and Storage:

It is recommended to consume all materials within 1 year of purchase. Tape should be stored in a cool, dry area (60°F - 80°F and 50%RH) and out of direct sunlight.

0.0015" 1000 Series 0 Aluminum Foil	
This Metal Can Be Certified To ASTM-B-479	
Technical Data	
Test Method/Performance Parameter	Result/Performance Properties
Tape Thickness Without Liner	2.4 mils. Nominal
Peel Adhesion	4.5 lbs./in.
Shear Adhesion	>24 hours @ 2.2 psi
Service Temperature	-30°F to 350°F (-34°C to 176°C)
Application Temperature	35°F to 100°F (0°C to 38°C)
Tested at 1.0 mil of adhesive on 2.0 mil polyester film to Stainless Steel.	

The information contained herein is derived from data believed to be reliable and is presented to assist our customers in determining whether our products are suitable for use in their application. We request that our customers test our products before use to satisfy themselves as to suitability for use. No warranty or guarantee is expressed or implied. Protection from any law or patents is not inferred. All patent rights are reserved. The exclusive remedy for all proven claims is limited to replacement of our materials and in no event shall we be liable for special, incidental, or consequential damages. Customers desiring assistance with specification, development or performance criteria for specific product applications should contact us for further information.