



PF-P.7 BOPP Film

Product Application & Description

PF-P.7 is a clear .7 mil. multi-purpose co-extruded biaxially oriented polypropylene (BOPP) film, suitable for use as a stand alone label material or in laminated multi-layer constructions. PF-P.7 is a strong, durable film that offers good die cutting performance and is available treated for print receptivity.

Shelf Life & Storage

It is recommended to consume all materials within 1 year from date of purchase. Best if stored in a controlled environment (72°F and 50% RH) and out of direct sunlight.

Technical Data	
Properties	Value
Film Haze	1.7 to 2.0%
Gloss, 45	80 to 85%
Tensile Strength (PSI)	17,000 MD/32,000 TD
Secant Modulus	270,000 MD/450,000TD
Ultimate Elongation (MD/TD)	585 MD/630 TD
Co-Efficient of Friction	0.3 to 0.4
<i>Tested in a normal laboratory condition: 23°C at 50% relative humidity.</i>	

Please Note: The information contained herein is derived from data believed to be reliable and is presented to assist our customers in determining whether our products are suitable for use in their application. We request that our customers test our products before use to satisfy themselves as to suitability for use. No warranty or guarantee is expressed or implied. Protection from any law or patents is not inferred. All patent rights are reserved. The exclusive remedy for all proven claims is limited to replacement of our materials and in no event shall we be liable for special, incidental or consequential damages. Customers desiring assistance with specification, development or performance criteria for specific product applications should contact us for further information.